



VIPER PEROXIBRIGHT CTG™

Peroxide Activated Concrete, Tile & Grout Cleaner and Brightener

- X Grout
- X Quarry Tile
- X Saltillo
- X Concrete
- X Ceramic Tile
- X Porcelain Tile

.....
X = Primary Use ✓ = Secondary Use



HYDRO-FORCE™

One U.S. Gallon (3.79 Litres)

RTU ph - 2.0 - 3.0

- Activated effervescent solution gets into every crevice, crack, and pore to effectively emulsify, dissolve and deflocculate the most stubborn soiling.
- Cleans and brightens without need for neutralization that harsh acids require.
- A proprietary mixture of specialized surfactants and non-butyl solvents is activated by a stabilized oxygenated solution.

DIRECTIONS FOR USE:

Read entire label before using. Use only as directed. Always pretest surface with cleaning solution for color-fastness prior to cleaning. Mask off all surfaces which may come in contact with prespray, especially metal. Wear protective eyewear, gloves, long sleeves, and long pants while handling concentrate. Ensure work area is well-ventilated during application and until surface is dry. Keep children and pets out of the area during application and drying.

1. For normal soiling, mix 32 ounces (1 quart) of solution with gallon of warm or hot water (1:4) into a professional plastic spray applicator. For heavy soiling, mix two quarts (64 ounces) of solution with a gallon of warm or hot water (1:2) into a professional spray applicator. For application through a Hydro-Force Inline Injection Sprayer, use straight solution into sprayer bottle. Use no metering tip for 1:4 mixture.
2. Apply mixed solution with sprayer evenly and liberally across surface to be cleaned. If preferred, you can apply mixed solution with a damp mop, sponge, or other appropriate professional equipment. If using a mop for solution application and surface cleaning, change your mop water often to make sure that soil is not redeposited. Agitate with a brush as needed. Brush agitation assists the cleaning process.
3. For best results, agitate and extract cleaning solution

using warm or hot water and a rotary agitation surface cleaner such as a Hydro-Force SX-15, SX-12 or SX-7. For tight spaces or especially sensitive surfaces, use the Hydro-Force Gekko Hard Surface Extraction Tool, or simply mop with rinse with clean warm or hot water.

4. Rinse the area thoroughly with water and allow to dry. Accelerate drying with air mover like the Hydro-Force Air King or OmniPro OmniDry Air Mover.

CONTAINS

Deionized water (C.A.S. #7732-18-5), Hydrogen Peroxide (C.A.S. 7722-84-1), nonionic surfactant, Sodium Xylene Sulfonate (C.A.S. #1300-72-7), Glycol Ether PM (C.A.S. #107-98-2), Glycol Ether DPNB (C.A.S. #29911-28-2).

INSTRUCCIONES:

1. Para lugares sucios, mezclar 32oz de solución con un galón de agua caliente. Usando un rociador de plástico profesional. Para lugares muy sucios, mezclar 64oz de solución con un galón de agua tibia o caliente, usando un rociador profesional. Para aplicar mediante un rociador inyector hydro-force, use la solución directa en la botella del rociador.
2. Aplique la solución mezclada con el rociador, en forma pareja en toda el área que desea limpiar. Y si se prefiere, se puede aplicar la solución mezclada con un trapeador húmedo. O una esponja o cualquier equipo profesional, si usa un trapeador para aplicar la solución en el área que desea limpiar, cambie seguido el agua para asegurarse que, el suelo quede completamente limpio. Agítese con un cepillo como sea necesario. El cepillo de agitación ayuda al proceso de limpieza. Agítese con un cepillo como sea necesario. El cepillo de agitación ayuda al proceso de limpieza.
3. Para mejores resultados, agite y extraiga la solución limpiadora usando agua tibia o caliente y una máquina de agitación rotatoria tal como hydro-force sx-15, sx-12, o sx-7. Para lugares poco espaciosos o que son pisos

delicados, use hydro-force gekko hard surface extraction tool, o simplemente use un trapeador con agua tibia o caliente y limpia.

4. Limpie el área con bastante agua y dejela secar, acelere el proceso de secado con un ventilador de hydro-force air king o un omnipro, omnidry air mover.

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to www.hydroforce.com/sds for additional safety, regulatory and liability information.

PEROXIBRIGHT CTG



May cause skin and eye irritation. Avoid contact with skin and eyes. In case of contact, immediately flush with plenty of water, seek medical advice if irritation persists.

Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médecin si l'irritation se fait persistante.

SEE SAFETY DATA SHEET
VOIR LA FICHE SIGNATÉTIQUE

See Safety Data Sheet (SDS):
www.hydroforce.com/sds
for additional safety and regulatory information.

Another fine product from Hydro-Force Manufacturing
4282 South 590 West, Salt Lake City, UT 84123
www.hydroforce.com

CAUTION!



Keep out of reach of children.

HAZARD STATEMENTS:

May cause or intensify fire; Oxidizer. May be corrosive to metals. Causes severe skin burns and eye damage. May cause respiratory irritation.

PRECAUTIONARY STATEMENTS:

Wear protective gloves/protective clothing/eye protection/face protection.

PRECAUCIÓN!




Mantener fuera del alcance de los niños.

INDICACIONES DE PELIGRO:

Puede causar o intensificar fuego; oxidante. Puede ser corrosivo para los metales. Causa quemaduras severas en la piel y daño a los ojos. Puede causar irritación respiratoria.

DECLARACIONES DE PRECAUCIÓN:

Usar guantes, ropa, lentes y mascarillas de protección.



V2

CH41GL