



SOLIDROCK PREMIUM STONE & GROUT SEALER

Water Based Sealer Repels Oil & Water Based Spills While
Resisting Soil & Stains

SOLIDROCK

Waterbased sealer which lets water vapor out but slows down the penetration of liquid. Outstanding on Stone, Grout and other porous tile.



RTU ph - 8.0

Contents: One U.S. Gallon (3.79 Litres)

- Bonding and protection technology that provides maximum protection against spots and spills
- Protects without affecting slip resistance
- Preserves the natural look of stone and can be applied to interior and exterior surfaces
- Ideal water based sealer formable, granite, limestone, saltillo, travertine, sandstone, and terrazzo

DIRECTIONS FOR USE:

Before Application

SHAKE THOROUGHLY BEFORE EACH USE!

Test for suitability in an inconspicuous area, especially for polished marble and extremely porous surfaces. Ensure that the area is well-ventilated during application and until the surface is dry. Keep children and pets out of the area until foot traffic resumes. Sealer may be applied to damp surfaces one hour after standing water has been removed. Surface temperature should be between 50°F and 80°F. Mask any surfaces not intended to be treated.

Cleaning is necessary

Surface must be cleaned and thoroughly rinsed. The drier the stone and grout, the better the penetration. Make sure that there are no puddles in grout lines and use air movers to speed the drying of the stone and grout lines before application. If pH of surface is higher than 11, (unusual if thoroughly rinsed), then sealer may not bond properly. Stone & grout lines may need to be rinsed with Spinergy Vivid Neutral Stone Cleaner/Rinse to lower pH of grout before applying sealer.

Dilution Instructions

Do not dilute. The product is ready to use. Coverage should be between 300 and 1200 sq. ft. per gallon depending on the porosity of the surfaces and the coverage required (grout only or entire surface).

Application Methods

Grout Application

Spray grout lines with pump up sprayer. Squeegee excess into untreated areas and bonnet off non-porous tiles. When dry (typically 1 to 2 hours) if there is a white haze on tiles, then buff off with white polishing pad and 175 rpm rotary machine.

Stone Application

For entire floor application, spray on sealer then spread with a brush with synthetic fibers. An alternative and sometimes preferred application method is to liberally apply an even coat using a paint pad, roller or brush. Allow sealer to penetrate the surface for 15-30

minutes. During this time, distribute sealer over entire area to ensure even penetration. Remove excess sealer by wiping entire surface thoroughly with clean, dry towels. A second coat may be necessary after 1 hour. Place drop of water on newly sealed grout or stone and see if it absorbs into grout or stone. If it does absorb readily, then a second coat is necessary.

Post Application Precautions

Floor is typically walkable in 3 to 4 hours, ready for use after 8 to 12 hours, and completely cured in 24 hours. These times will be shorter if only grout was sealed. After 6 to 18 months, reapplication may be necessary, depending upon the traffic level, maintenance procedures and the type of surface sealed.

CONTAINS

Water (CAS# 7732-18-5), Proprietary C6 fluorochemical resin, Isopropyl Alcohol (CAS# 67-63-0)

INSTRUCCIONES PARA SU USO

Antes de usarse agítese bien la botella. Haga una prueba preliminar de la compatibilidad del producto, en un área poco visible, especial para pulir el mármol y extremadas superficies porosas. Asegúrese que el área está ventilada durante la aplicación y hasta que se seque. Mantenga a los niños y mascotas fuera del área. El sellador se puede aplicar una hora después de que toda el agua ha sido removida. Temperatura de la superficie debe estar entre 50 y 80 grados F.

Limpieza es necesaria :

La superficie debe estar limpia. Entre más limpia y seca este el área mejores resultados tendrá. Asegúrese que las líneas del grout estén limpias y use aire para secar más rápido el área antes de la aplicación del producto. Y si el pH de la superficie es más de 11, entonces el sellador no va a funcionar apropiadamente. El piso tal vez deba ser limpiado con Spinergy Vivid Neutral Stone Cleaner/Rinse para bajar el pH del piso antes de aplicar este producto.

Instrucciones de dilucion

No se diluya. El producto está listo para usarse. La botella alcanza a cubrir un área de 300 a 1200 sq. ft por un galon dependiendo de que tan brillante quiera. (solo grout y superficies de piedra)

Metodos de aplicacion

Aplicacion en grout: Use un rociador de bomba para aplicarlo en las líneas de grout. Seque el exceso con un trapo. Se seca en 1 a 2 horas y si quedo algo blanco en el azulejo, entonces tiene que pulir con una maquina rotatoria de 175 rpm.

Aplicacion en piedra: Para todo el piso, rocíe el sellador y use un

cepillo de fibra sintetica para expandir el sellador. También puede usar un rodillo, o una brocha de pintar. Permita que el sellador penetre en la superficie por 15 a 30 minutos. Durante este tiempo, distribuya el sellador sobre toda el área para asegurar una penetración pareja. Remueva el exceso de sellador con una toalla limpia. Tal vez necesite una segunda aplicación después de 1 hora. Ponga unas gotas de agua sobre el Nuevo sellador en el piso y vea si lo absorbe si es así entonces debe aplicarse una segunda vez.

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to www.bridgepoint.com/sds for additional safety, regulatory and liability information.

SOLIDROCK



May cause skin and eye irritation. Avoid contact with skin and eyes. In case of contact, immediately flush with plenty of water, seek medical advice if irritation persists.

Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médecin si l'irritation se fait persistante.

SEE SAFETY DATA SHEET
VOIR LA FICHE SIGNATÉTIQUE

See Safety Data Sheet (SDS):

www.bridgepoint.com/sds

for additional safety and regulatory information.

Another fine product from Bridgepoint Systems
4282 South 590 West, Salt Lake City, UT 84123

www.bridgepoint.com

WARNING!



Keep out of reach of children.

HAZARD STATEMENTS:

Causes eye irritation.

PRECAUTIONARY STATEMENTS:

IF IN EYES: Rinse cautiously with water for several minutes. Remove Contact Lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF SKIN irritation occurs: Get medical advice/attention.

ADVERTENCIA!



Mantener fuera del alcance de los niños.


INDICACIONES DE PELIGRO:

Causa irritación al ojo.

DECLARACIONES DE PRECAUCIÓN:

Si en los ojos: Enjuagarse cuidadosamente con agua por varios minutos. Remueva lentes de contacto si los está usando. Continúe enjugándose. Si en la piel: Lavarse con amplio jabón y agua. Si irritación a la piel ocurre: Obtenga consejo/ atención médica.

FLAMMABILITY



CST20GL