



# Hardwood Preservation GLOSS Finish

- Hardwood Floors
- Cabinets
- Furniture

Contents: One U.S. Gallon (3.79 Litres)

- Designed to be used as a preservation finish over an existing urethane finish over a hardwood floor

- Low solid blend of urethane and acrylic

- Serves as the wear coat and protects the original finish of the floor



## Extraction Cleaning

- Vacuum floor thoroughly.
- Mask off transitions from wood to other types of floors.
- Mix one part Heavy Duty Hardwood Cleaner with 4 parts warm water in the cleaning machine. Adding a defoamer like Foamless to the waste tank is recommended for some machines and situations.
- With the solution pumping, the brush rotating and the vacuum turned on, begin moving the machine forward at a moderate speed. Reverse on the same line at the same speed. Then continue into the next area with the same procedure. Remove any standing solution with an absorbent flat mop.
- Mix one part Wood Fresh™ Hardwood Cleaner with 4 parts warm water in the cleaning machine
- Proceed to clean and neutralize the complete floor in the same manner as explained above.
- The cleaning and preparation steps are important. The dual cleaners both clean and treat the floor to make it more receptive to the Preservation Finish. Apply finish immediately after cleaning

approximately 1,000 sq. ft.

## Apply Preservation Finish

- Let the customer choose Gloss or Satin finish. Solids may settle to bottom of gallon over time. Shake or stir before and during use.
- The finish may be applied with a dampened flat mop using either a clean cotton terry cloth cover or a microfiber cover. 30 minutes prior to applying the finish the container should be gently rocked to mix the ingredients.
- Start in the furthest area from your exit. Apply a small amount of finish in a 4 or 5 foot area, spreading it uniformly as you work your way back toward the exit door.
- If a second coat is desired, allow one hour before applying.
- Use abrasive cleaning method when applying finish to cabinets and furniture.



## Helpful Hints

- Traffic: Allow one hour dry time before allowing stocking feet onto the finish. Allow 24 hours before shoe traffic and replacing furniture. Allow 48 hours before replacing rugs.
- Prequalify: The system emphasizes the importance of preserving the original finish so hopefully the customer will never have to go through the messy process of sanding and recoating their hardwood. This system does not make damaged or heavily scratched floors look like new. We suggest you

under promise and then over perform.  
• Coverage: Approximately 1,000 sq. feet per gallon

## CONTAINS:

Water (CAS # 7732-18-5), Proprietary Urethane Polymers, Proprietary Acrylic Polymers, Tributoxyehtyl phosphate (CAS # 78-53-1).

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to [www.hydroforce.com/sds](http://www.hydroforce.com/sds) for additional safety, regulatory and liability information.

## HARDWOOD PRESERVATION - GLOSS



May cause skin and eye irritation. Avoid contact with skin and eyes. In case of contact, immediately flush with plenty of water, seek medical advice if irritation persists.

Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médecin si l'irritation se fait persistante.

SEE SAFETY DATA SHEET  
VOIR LA FICHE SIGNATÉTIQUE

See Safety Data Sheet (SDS):  
[www.hydroforce.com/sds](http://www.hydroforce.com/sds)  
for additional safety and regulatory information.

Another fine product from Hydro-Force Manufacturing  
4282 South 590 West, Salt Lake City, UT 84123  
[www.hydroforce.com](http://www.hydroforce.com)

## WARNING!!



Keep out of reach of children.

## HAZARD STATEMENTS:

Causes serious eye irritation.  
Causes skin irritation.

## PRECAUTIONARY STATEMENTS:

Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. IF ON SKIN: Wash with plenty of soap and water. IF SKIN irritation occurs: Get medical advice/attention. Remove Contact Lenses, if present and easy to do. Continue rinsing.

## ADVERTENCIA!!



Mantener fuera del alcance de los niños.

## INDICACIONES DE PELIGRO:

Causa irritación severa al ojo. Causa irritación a la piel.

## DECLARACIONES DE PRECAUCIÓN:

Lavar bien las manos después de usar. Usar guantes, ropa, lentes y mascarillas de protección. Si en los ojos: Enjuagarse cuidadosamente con agua por varios minutos. Remueva lentes de contacto si los está usando. Continúe enjugándose. Si en la piel: Lavarse con amplio jabón y agua. Si irritación a la piel ocurre: Obtenga consejo/ atención médica.

FLAMMABILITY

