

92-600

Disposable Nitrile Glove with Enhanced Chemical Splash Protection

The world's leading disposable glove for chemical splash protection

- Proprietary Ansell material formulation offers enhanced chemical splash protection
- Soft nitrile provides high levels of comfort
- Robust design for superior durability
- Silicone free design is paint and finish process friendly
- Also available in packaging to fit vending machines

TOUCHNTUFF 92 600 F png

Industries

- Life Sciences
- Food Processing
- Automotive
- Machinery and Equipment
- Chemical

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Meat, Fish and Food Processing
- Industrial Production
- Maintenance
- Laboratory analysis
- Chemical Handling

TouchNTuff 92-600 Glove Box

WWW.ANSELL.COM

92-600

Disposable Nitrile Glove with Enhanced Chemical Splash Protection

Technical Data Sheet

Product Information

92-600

Material	Nitrile
Color	Green
Glove Design	Powder-Free, Chlorinated, Silicone Free, Smooth

Cuff	Beaded
Manufacturing/QMS Audit Standards	ISO 9001:2008
Regulatory/Standards Compliance	Category III, EAC TP TC 019:2011, EN 374:2003, EN ISO 374-1:2016, EN 420:2003 + A1:2009, EN ISO 374-5:2016, FDA21 CFR 177-2600, ISO 9001
Packaging	100 gloves per dispenser; 10 dispensers/1000 gloves per case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia, Sri Lanka, Thailand
User Needs Segment	Robust
Available sizes	S (6.5 - 7), M (7.5 - 8), L (8.5 - 9), XL (9.5 - 10)
Anti-static	Yes

Physical Properties

	Typical Values		Testing Method
Length (mm/inches)	240 / 9.5		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	4.0 AQL (North & South America) / 1.5 AQL (Europe, Middle East, Africa, Asia, Pacific)		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.12 / 4.7		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.16 / 6.2		ASTM D3767,EN 420
	Before Aging	After Aging	
Ultimate Tensile Strength (MPa) \geq 18		\geq 18	ASTM D412 & D573
Elongation at Break (%) \geq 500		\geq 400	ASTM D412
Force at break (N) \geq 6		\geq 6	EN 455-2

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	585834	585835	585836	585837

Technology

□

For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region

- Ansell Healthcare Europe NV
- T: +32 (0) 2 528 74 00
- F: +32 (0) 2 528 74 01

Asia Pacific Region

- Ansell Global Trading Center (Malaysia) Sdn Bhd

- T: +603 8310 6688
- F: +603 8310 6699

North America Region

- Ansell Healthcare Products LLC
- T: +1 800 800 0444
- F: +1 800 800 0445

Latin America & Caribbean Region

- Ansell Commercial Mexico S.A. de C.V.
- T: +52 442 248 1544 / 248 3133

Australia

- Ansell Limited
- T: +61 1800 337 041
- F: +61 1800 803 578

Russia

- Ansell PYC
- Ten. +7 495 258 13 16

Performance Standards and Regulatory Compliance

EN374_LowChemicalResistance

EN 374 Microorganism

J K P T

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

□