

Penewet is a ready-to-use, colorless wetting agent/surfactant solution incorporating advanced concepts in surface chemistry. It provides superior wetting, penetrating and coalescing of Asbestos Containing Material (ACM) to permit handling and removal of these materials under damp, dust-free conditions. Penewet is a non-flammable, water based liquid that will not corrode aluminum components of spray equipment.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Stir Penewet thoroughly to achieve a uniform consistency. Penewet is pre-mixed, water addition is not necessary.

APPLICATION TOOLS

Apply Penewet with an airless or pump sprayer.

PRODUCT APPLICATION

Apply Penewet initially at full strength. Wait a few minutes after the first application and re-spray to ensure adequate penetration and saturation of ACM. After determining the proper rate of spray that is effective for the removal of the ACM, and documenting acceptable fiber count levels. Air monitoring results will determine the suitability of this procedure.

COVERAGE

Depending on thickness and porosity of the material, coverage should not be less than 500 sq. ft. per gallon.

CLEANUP

Tools and drippings should be rinsed with warm soapy water. Follow equipment manufacturer's directions to clean spray equipment. Dispose of contents/container according to all local, state and federal regulations. Store in a closed container. Keep from freezing. Store between 40°F (4.5°C) and 90°F (32°C).

PRECAUTIONS

Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn.

Asbestos abatement activities must be performed in accordance with all applicable regulations including EPA, OSHA, Federal, State and Local. For more information always contact the appropriate agencies prior to beginning any abatement project.



Professional Products
Professional Results



WETTING AGENT & SURFACTANT

Keeps ACM Wet More Than 5 times Longer Than Other Detergents

- Ready to use formula
- Satisfies NESHAP requirements
- Penetrates and wets out asbestos creating a damp, dust free environment

NET CONTENTS: 5 Gallons

For Professional Use Only

Asbestos Abatement Products

FIBERLOCK PENEWET RTU 6450
WARNING | ATTENTION

H320 - Causes eye irritation.

Wash all exposed external body areas thoroughly after handling.; See SDS for full list of P phrases

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; If eye irritation persists: Get medical advice/attention.; See SDS for full list of P phrases

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

H320 - Provoque une irritation des yeux

Se laver toutes les zones du corps exposées externes soigneusement après manipulation.[Voir SDS pour la liste complète des phrases P

EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer.[Si l'irritation oculaire persiste: consulter un médecin.[Voir SDS pour la liste complète des phrases P

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

PENE WET, the PENE WET Logo and other marks on this label are trademarks of ICP Construction, Inc.

6450-5



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 10.17.18