

## Dehumidifiers

### DriTec® 4000i Desiccant

Powerful, versatile desiccant dehumidification. Easy setup and smart controls. Monitor system performance, and set minimum and maximum humidity levels to eliminate concerns about over-drying – no other desiccants offer this feature!

Visit our blog for tips and insights about desiccant dehumidifiers [here](#).

### Features

- Smart controls deliver optimized performance
- Onboard min/max humidistat controls and pints-per-day display
- 33% smaller than closest competitor
- Equipped with Positive Thermal Coefficient heaters for better efficiency, safety and longer life
- Sturdy and highly portable – even works on its back for low-clearance areas
- Rugged vacuum-molded back protects the unit for loading and transport
- Built-in compartment provides storage for power cords and ducting
- Handy on-unit guide for ducting setup

### Specifications

- **Water removal (at 80°F/60%RH):** 118 pts./day | 55.8 L per/day
- **Process Air:** 395 CFM
- **Reactivation Air:** 65 CFM
- **Dimensions (W × H × D):**  
21.14 × 33.13 × 20.25 in. (with handle upright = 42. 250 in.)  
53.7 × 84.15 × 51.4 cm (with handle upright = 107.3 cm.)
- **Weight:** 95 lbs. | 43.1 kg
- **Volts:** 115V
- **Frequency:** 60 Hz
- **Amps (at 80°F/60%RH):**  
Circuit 1: 12  
Circuit 2: 12
- **Air filter:** 4-PRO filter
- **Safety:** ETL listed to CSA dehumidifier standards
- **Xactimate:** WTRDHM

### Sizes ▪ Options

- 114621 (F533): One unit