

# BUILT TOUGH AND EASY TO SERVICE

**STRIKE FIRST ABC MULTI-PURPOSE DRY CHEMICAL  
FIRE EXTINGUISHERS ARE DESIGNED FOR:**



WOOD,  
PAPER,  
CLOTH

**CLASS A**



FLAMMABLE  
LIQUIDS  
& GASES

**CLASS B**



ELECTRICAL  
CONDUCTIVITY

**CLASS C**

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- Waterproof stainless steel gauge
- Reinforced, full grip stainless steel handles
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar coded labels for accurate service



LISTED

**MEETS OR EXCEEDS:**  
ANSI/UL 299 & 711



LISTED  
HOMOLOGUÉ

**MEETS OR EXCEEDS:**  
CAN/ULC-S504 & S508



**STRIKE FIRST**  
CORPORATION

MANUFACTURING FIRE EQUIPMENT FOR OVER 35 YEARS

**MULTI-PURPOSE**  
**ABC DRY CHEMICAL**

- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)



CAPACITY	2.5 lbs.	5 lbs.	5 lbs.	10 lbs.	20 lbs.	30 lbs.
Model No.	SF-ABC110ST	SF-ABC310	SF-ABC340	SF-ABC680	SF-ABC1020	SF-ABC30
UL/ULC Rating	1-A : 10-B : C	3-A : 10-B : C	3-A : 40-B : C	6-A : 80-B : C	10-A : 120-B : C	10-A : 120-B : C
U.S.C.G. Approval	Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size I	Type A Size II, Type B:C Size II	Type A Size II, Type B:C Size III	Type A Size II, Type B:C Size IV
Range	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	8-10 ft (2.5-3 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)	10-15 ft (3-4.5 m)
Discharge Time	9 sec	13 sec	13 sec	15 sec	28 sec	28 sec
PSI	150	195	195	235	235	195
Height	15 1/4" (39 cm)	15 1/4" (39 cm)	16 7/8" (43 cm)	21 1/4" (54 cm)	24" (61 cm)	30 3/4" (78 cm)
Width	3 3/4" (9.5 cm)	6 3/4" (17 cm)	6 3/4" (17 cm)	8" (20.3 cm)	9 1/2" (24 cm)	9 1/2" (24 cm)
Diameter	3 1/8" (8 cm)	4 1/4" (11 cm)	4 1/4" (11 cm)	5 1/8" (13 cm)	7 1/8" (18 cm)	7 1/8" (18 cm)
Weight	4 1/2 lb (2 kg)	10 1/2 lb (4.8 kg)	10 1/2 lb (4.8 kg)	19 1/4 lb (8.8 kg)	35 1/4 lb (16.1 kg)	50 1/3 lb (22.8 kg)
Chrome Option	YES	-	YES	-	-	-
Standard Bracket	Vehicle/Marine	Wall or Vehicle/Marine	Wall or Vehicle/Marine	Wall	Wall	Wall
Optional Brackets	Wall UP2-DB	UB-5DB UB-5MD HDVB-1	UB-5DB UB-5MD HDVB-1	UP-10MD HDVB-2	HDVB-3	HDVB-4 HD-CART



**STRIKE FIRST**  
CORPORATION

777 Tapscott Road  
Scarborough  
Ontario, Canada M1X 1A2

P 416 299-7767  
TF 1 888 575-1132  
F 416 299-8039  
TF 1 888 575-1134

[info@strike-first.com](mailto:info@strike-first.com) | [strike-first.com](http://strike-first.com)