


Double-Sided Sheeting Tape



Carrier: Cloth/Paper Lamination

Adhesive: Differential Rubber

Liner: Blue LDPE

Colors: Natural/Blue

Specifications: N/A

Standard Sizes: 48mm x 20Yd

Applications

 Securing tarps or poly sheeting materials to surfaces such as wood, glass, aluminum, plastics, and vinyl Holds materials in place without damaging surfaces for painting, cleaning, sanding, construction, or abatement applications

Features Benefits

Cloth reinforcement	 Hand teable and durable like duct tape 	
	 Conformable and moisture resistant 	
 Differential Adhesive 	 Provides aggressive bond to tarps and sheeting 	
	 Blue side removes clean from surfaces for up 	
	to 14 days	
	 High strength to hang heavy sheeting materials 	
Release Liner	Fasy to remove leasy to use	

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	15.0 mils	0.381 mm	ASTM D-1000
Adhesion to Steel (air side)	25 oz/in	2.74 N/cm	PSTC-101
Adhesion to Steel (liner side)	40 oz/in	4.38 N/cm	PSTC-101
Tensile Strength	63 lb/in	110.33 N/cm	ASTM D-1000
Shear Strength	10000+ hrs		
Elongation	11%		

Recommended Storage Conditions: 60-80 $^{\circ}$ F at 40-60% RH Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

