

MANUFACTURINGFIREEQUIPMENTFOROVER35YEARS

BUILT TOUGH AND EASY TO SERVICE

STRIKE FIRST REGULAR BC DRY CHEMICAL FIRE EXTINGUISHERS ARE DESIGNED FOR:



FLAMMABLE LIQUIDS & GASES



ELECTRICAL CONDUCTIVITY

LASS B



Super durable polyester powder paint finish with superior corrosion resistance

- Waterproof stainless steel gauge
- Handle reinforced, full grip hardcoat anodized aluminum
- Oversized pull pin with retaining strap for easier and faster activation
- · Color and bar coded labels for accurate service
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- · U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)





MEETS OR EXCEEDS: ANSI/UL 299 & 711



MEETS OR EXCEEDS: CAN/ULC-S504 & S508



MANUFACTURINGFIREEQUIPMENTFOROVER35YEARS

- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- U.S.C.G. approved with bracket listed on label
- Temperature range: -65°F to 120°F (-54°C to 49°C)





