Revision Date: 03/17/2020

# SAFETY DATA SHEET

#### 1. Identification

Product identifier: CHEMSAFE RAM-TACK SPRAY ADHESIVE - 57002

Other means of identification

**SDS number:** RE1000035655

Recommended restrictions
Product Use: Adhesive

Restrictions on use: Not known.

# Manufacturer/Importer/Distributor Information

#### Manufacturer

Company Name: Aramsco, Inc

Address: 1480 Grandview Ave

Paulsboro, NJ 08066

Telephone: 856-686-7801

Fax:

Emergency telephone number: 1-866-836-8855

# 2. Hazard(s) identification

#### **Hazard Classification**

# **Physical Hazards**

Flammable aerosol Category 1

**Health Hazards** 

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Specific Target Organ Toxicity - Category 3<sup>1</sup>

Single Exposure

Aspiration Hazard Category 1

## **Target Organs**

Narcotic effect.

#### **Environmental Hazards**

Acute hazards to the aquatic Category 3

environment

Chronic hazards to the aquatic Category 3

environment

#### **Label Elements**

### **Hazard Symbol:**



Signal Word: Danger

Revision Date: 03/17/2020

**Hazard Statement:** Extremely flammable aerosol.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors

or in a well-ventilated area. Avoid release to the environment.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water If skin irritation or rash occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

#### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Propane	74-98-6	20 - <50%
2-Propanone	67-64-1	20 - <50%
Butane	106-97-8	10 - <20%
Heptane, branched, cyclic and linear	426260-76-6	5 - <10%
Heptane	142-82-5	5 - <10%
Naphtha (petroleum), hydrotreated light	64742-49-0	5 - <10%
Solvent naphtha (petroleum), light aliph.	64742-89-8	5 - <10%
Acetic acid, methyl ester	79-20-9	1 - <5%
Maleic Anhydride Modified Liquid Polyisoprene	841251-34-1	1 - <5%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

**Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

**Inhalation:** Move to fresh air.

Revision Date: 03/17/2020

**Skin Contact:** Get medical attention. Destroy or thoroughly clean contaminated shoes.

Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction

develops, get medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

**Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Absorb spill with vermiculite or other inert material, then place in a container

Methods and material for containment and cleaning

for chemical waste.

**Notification Procedures:** 

Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

can do so without risk.

Revision Date: 03/17/2020

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

# 7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin. Avoid contact with

eyes, skin, and clothing.

Conditions for safe storage,

including any incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 2

## 8. Exposure controls/personal protection

#### **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	Туре	Exposure Limit Values	Source
Propane	REL	1,000 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 1,800 mg/m3 ppm	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 1,800 mg/m3 ppm	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
2-Propanone	STEL	1,000 2,400 mg/m3 ppm	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	1,000 2,400 mg/m3 ppm	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	250 ppm	US. ACGIH Threshold Limit Values (03 2015)
	TWA	750 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm	US. ACGIH Threshold Limit Values (03 2015)
	REL	250 ppm 590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Naphtha (petroleum), hydrotreated light	PEL	100 ppm 400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
	REL	100 ppm 400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	100 ppm 400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Solvent naphtha (petroleum), light aliph.	REL	100 ppm 400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	100 ppm 400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	100 ppm 400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Heptane	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	85 ppm 350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm	US. ACGIH Threshold Limit Values (02 2012)
	STEL	500 ppm	US. ACGIH Threshold Limit Values (02 2012)
	Ceil_Time	440 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Acetic acid, methyl ester	REL	200 ppm 610 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	250 ppm 760 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	200 ppm 610 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	250 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	200 ppm 610 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	250 ppm 760 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	200 ppm	US. ACGIH Threshold Limit Values (2008)
Methanol	REL	200 ppm 260 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	200 ppm 260 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	200 ppm 260 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	250 ppm 325 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	200 ppm	US. ACGIH Threshold Limit Values (2008)

Revision Date: 03/17/2020

	STEL	250 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	250 ppm	325 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
20200, 0).	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29
			3. 3.	CFR 1910.1000) (02 2006)
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	20 ppm	•	US. ACGIH Threshold Limit Values (12 2010)
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX.	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	CONC			
_	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Benzene	REL	0.1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29
	00114	0.5		CFR 1910.1001-1053) (02 2006)
	OSHA_A	0.5 ppm		US. OSHA Specifically Regulated Substances (29
	TWA	10 nnm		CFR 1910.1001-1053) (02 2006) US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX.	10 ppm 50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	CONC	эо ррпі		03. OSHA Table 2-2 (29 CFK 1910.1000) (02 2000)
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29
		, ppiii		CFR 1910.1001-1053) (02 2006)
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Benzene, (1-methylethyl)-	REL	50 ppm	245 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
, , , , , , , , , , , , , , , , , , , ,	TWA	50 ppm		US. ACGIH Threshold Limit Values (2008)
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29
			· ·	CFR 1910.1000) (02 2006)
	TWA	50 ppm	245 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1 ppm		US. ACGIH Notice of Intended Changes (NIC) to
				Threshold Limit Values (03 2018)
Hexane	TWA	50 ppm	180 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	500 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29
				CFR 1910.1000) (02 2006)
	REL	50 ppm	180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	50 ppm		US. ACGIH Threshold Limit Values (2008)
Cyclohexane	TWA	100 ppm	4.050 / 0	US. ACGIH Threshold Limit Values (2008)
	TWA	300 ppm	1,050 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	300 ppm	1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	300 ppm	1,050 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29
Dhanal	T)A/A	F		CFR 1910.1000) (02 2006)
Phenol	TWA REL	5 ppm 5 ppm	10 ma/m2	US. ACGIH Threshold Limit Values (2008)
			19 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	Ceil_Time PEL	15.6 ppm	60 mg/m3 19 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005) US. OSHA Table Z-1 Limits for Air Contaminants (29
	FLL	5 ppm	19 1119/1113	CFR 1910.1000) (02 2006)
	TWA	5 ppm	19 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Benzene, ethenyl-	REL	50 ppm	215 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Donzono, outonyr	TWA	50 ppm	215 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	20 ppm	210 mg/m3	US. ACGIH Threshold Limit Values (2008)
	STEL	100 ppm	425 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	40 ppm	0g/1110	US. ACGIH Threshold Limit Values (2008)
	STEL	100 ppm	425 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	120 mg/mo	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	Ceiling	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX.	600 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	CONC	PP'''		(02 2000)
	TWA	2 ppm		US. ACGIH Notice of Intended Changes (NIC) to
		''		Threshold Limit Values (03 2018)
				<u>-</u>

# **Biological Limit Values**

Chemical Identity	Exposure Limit Values	Source
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL (03 2015)
Methanol (methanol: Sampling time: End of shift.)	15 mg/l (Urine)	ACGIH BEL (03 2013)

Revision Date: 03/17/2020

Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid:	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)
Sampling time: End of shift.)	0.00 // (11-/)	A O O U L D E L (00 0040)
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 μg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 μg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End	0.5 mg/l (Urine)	ACGIH BEL (03 2018)
of shift.)		
Phenol (Phenol with hydrolysis: Sampling time: End of shift.)	250 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, ethenyl- (styrene: Sampling time: End of shift.)	40 μg/l (Urine)	ACGIH BEL (03 2015)
Benzene, ethenyl- (Mandelic acid plus phenylglyoxylic acid:	400 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Sampling time: End of shift.)		

Appropriate Engineering

No data available.

**Controls** 

#### Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

> ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

Eye/face protection: Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** No data available.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear,

and protective clothing appropriate for the risk of exposure. Contact health

and safety professional or manufacturer for specific information.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When

using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed

out of the workplace.

#### 9. Physical and chemical properties

**Appearance** 

Physical state: liquid

Form: Spray Aerosol Color: No data available. Odor: No data available. **Odor threshold:** No data available. pH: No data available. Melting point/freezing point: No data available. Initial boiling point and boiling range: No data available. Flash Point: Estimated -104.44 °C

**Evaporation rate:** No data available.

No data available. Flammability (solid, gas):

Revision Date: 03/17/2020

#### Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): Estimated 9.5 %(V)
Flammability limit - lower (%): Estimated 1.9 %(V)
Explosive limit - upper (%): No data available.
Explosive limit - lower (%): No data available.

**Vapor pressure:** 4,481 - 5,860 hPa (20 °C)

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Viscosity:
7 - 200 mm2/s

#### 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

**Products:** 

No data available.

### 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

**Ingestion:** No data available.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Inhalation:** No data available.

**Skin Contact:**No data available.
Eye contact:
No data available.

**Ingestion:** No data available.

#### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

Oral

**Product:** Not classified for acute toxicity based on available data.

Revision Date: 03/17/2020

Specified substance(s):

2-Propanone LD 50 (Rat): 5,800 mg/kg

Heptane, branched, cyclic and linear

LD 50: > 2,000 mg/kg

Heptane LD 50 (Rat): > 5,000 mg/kg

Naphtha (petroleum), hydrotreated light

LD 50 (Rat): > 5,000 mg/kg

Solvent naphtha (petroleum), light aliph.

LD 50 (Rat): > 5,000 mg/kg

Acetic acid, methyl ester LD 50 (Rat): 6,482 mg/kg

Maleic Anhydride Modified Liquid Polyisoprene LD 50: > 5,000 mg/kg

**Dermal** 

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone LD 50 (Rabbit): > 7,426 mg/kg

Heptane, branched, cyclic and linear

LD 50: > 2,000 mg/kg

Heptane LD 50 (Rabbit): > 2,000 mg/kg

Naphtha (petroleum), hydrotreated light

LD 50 (Rabbit): > 3,750 mg/kg

Solvent naphtha (petroleum), light aliph.

LD 50 (Rabbit): > 3,000 mg/kg

Acetic acid, methyl ester LD 50 (Rat): > 2,000 mg/kg

Maleic Anhydride Modified Liquid Polyisoprene LD 50: > 5,000 mg/kg

Inhalation

**Product:** Not classified for acute toxicity based on available data.

Specified substance(s):

Heptane, branched,

cyclic and linear

Propane LC 50: > 100 mg/l

LC 50: > 100 mg/l

2-Propanone LC 50 (Rat): 50.1 mg/l

LC 50: > 5 mg/l

Butane LC 50: > 100 mg/l LC 50: > 100 mg/l

> LC 50: > 20 mg/l LC 50: > 5 mg/l

Heptane LC 50 (Rat): > 29.29 mg/l

LC 50: > 100 mg/l

Revision Date: 03/17/2020

Naphtha (petroleum), LOAEL (Human): 2,400 mg/m3 hydrotreated light LC 50 (Rat): > 7,630 mg/m3

LC 50: > 5 mg/l

Solvent naphtha LC 50: > 100 mg/l (petroleum), light aliph. LC 50: > 100 mg/l

Acetic acid, methyl ester LC 50: > 49.2 mg/l

LC 50: > 5 mg/l

Maleic Anhydride LC 50: > 100 mg/l Modified Liquid LC 50: > 100 mg/l Polyisoprene

Repeated dose toxicity

**Product:** No data available.

Specified substance(s):

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

2-Propanone NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental

result, Key study

Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

Heptane NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental

result, Key study

Naphtha (petroleum), hydrotreated light

LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Readacross based on grouping of substances (category approach), Key study

NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal

Experimental result, Supporting study

NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation

Experimental result, Key study

Solvent naphtha (petroleum), light aliph.

NOAEL (Mouse, Rat(Female, Male), Inhalation, 107 - 113 Weeks): 1,402

mg/m3 Inhalation Experimental result, Key study

NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal

Experimental result, Key study

NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal

Experimental result, Supporting study

Acetic acid, methyl ester NOAEL (Rat(Female, Male), Inhalation, 28 d): 350 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, 28 d): 2,000 ppm(m) Inhalation

Experimental result, Key study

Skin Corrosion/Irritation

**Product:** No data available.

Specified substance(s):

2-Propanone in vivo (Rabbit): Not irritant Experimental result, Supporting study

Heptane in vivo (Rabbit): Irritating Read-across based on grouping of substances

(category approach), Key study

Acetic acid, methyl

ester

in vivo (Rabbit): Not irritant Experimental result, Key study

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Revision Date: 03/17/2020

#### Specified substance(s):

2-Propanone Irritating.

Rabbit, 24 hrs: Minimum grade of severe eye irritant

Heptane Rabbit, 24 - 72 hrs: Not irritating

Naphtha (petroleum), hydrotreated light

Rabbit, 24 - 72 hrs: Not irritating

Solvent naphtha

(petroleum), light aliph.

Rabbit: Not irritating

Acetic acid, methyl

Rabbit: Irritating

ester

# Respiratory or Skin Sensitization

**Product:** No data available.

Specified substance(s):

2-Propanone Skin sensitization:, in vivo (Guinea pig): Non sensitising Skin sensitization:, in vivo (Guinea pig): Non sensitising Skin sensitization:, in vivo (Guinea pig): Non sensitising Skin sensitization:, in vivo (Guinea pig): Non sensitising

hydrotreated light

Solvent naphtha Skin sensitization:, in vivo (Guinea pig): Non sensitising

(petroleum), light aliph.

Carcinogenicity

**Product:** No data available.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

#### **US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

#### **Germ Cell Mutagenicity**

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

# Specific Target Organ Toxicity - Single Exposure

**Product:** No data available.

Specified substance(s):

2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Heptane Narcotic effect. - Category 3 with narcotic effects.

#### **Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

#### **Target Organs**

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Revision Date: 03/17/2020

**Aspiration Hazard** 

**Product:** No data available.

Specified substance(s):

Heptane, branched, cyclic

May be fatal if swallowed and enters airways.

and linear

Heptane Naphtha (petroleum), May be fatal if swallowed and enters airways. May be fatal if swallowed and enters airways.

hydrotreated light

Solvent naphtha

May be fatal if swallowed and enters airways.

(petroleum), light aliph.

Other effects: No data available.

#### 12. Ecological information

#### **Ecotoxicity:**

#### Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Specified substance(s):

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key

study

Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Heptane LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality

Naphtha (petroleum), hydrotreated light

LC 50 (96 h): 8.41 mg/l Experimental result, Key study

Acetic acid, methyl ester LC 50 (Fathead minnow (Pimephales promelas), 96 h): 295 - 348 mg/l

Mortality

LC 50 (Danio rerio, 48 h): 250 - 350 mg/l Experimental result, Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Specified substance(s):

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Butane LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study

Heptane EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Solvent naphtha EC 50 (Daphnia magna, 48 h): 32 mg/l Experimental result, Supporting

(petroleum), light aliph. study

Acetic acid, methyl ester EC 50 (Daphnia magna, 48 h): 1,026.7 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

Revision Date: 03/17/2020

Specified substance(s):

Heptane NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna): 10 mg/l Other, Key study NOAEL (Daphnia magna): 2.6 mg/l Other, Key study

**Aquatic Invertebrates** 

Product: No data available.

Specified substance(s):

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Heptane, branched, cyclic and linear

NOEC: < 1 mg/l estimation

NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of Heptane

substances (category approach), Key study

EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of

substances (category approach), Key study

Naphtha (petroleum), hydrotreated light Solvent naphtha (petroleum), light aliph. EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study EC 50 (Daphnia magna): > 40 mg/l Experimental result, Key study

**Toxicity to Aquatic Plants** 

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Butane 100 % (385.5 h) Detected in water. Experimental result, Key study

Heptane 70 % Detected in water. Experimental result, Key study

Naphtha (petroleum). hydrotreated light

90.35 % (28 d) Detected in water. Experimental result, Supporting study

Solvent naphtha

(petroleum), light aliph.

90.35 % (28 d) Detected in water. Experimental result, Supporting study

Acetic acid, methyl ester 70 % Detected in water. Experimental result, Key study

**BOD/COD Ratio** 

Product: No data available.

Bioaccumulative potential

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Specified substance(s):

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment

Experimental result, Not specified

Revision Date: 03/17/2020

Heptane Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by

calculation, Key study

Naphtha (petroleum), hydrotreated light

Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

calculation, Key study

Solvent naphtha

Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

(petroleum), light aliph. calculation, Key study

# Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Specified substance(s):

Naphtha (petroleum), Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study hydrotreated light Log Kow: 2.2 - 5.2 23 °C Yes Experimental result, Key study

Log Kow: 2.2 - 6.1 23 °C Yes Experimental result, Key study

**Mobility in soil:** No data available.

Known or predicted distribution to environmental compartments

Propane No data available. 2-Propanone No data available. **Butane** No data available. Heptane, branched, cyclic and linear No data available. Heptane No data available. Naphtha (petroleum), hydrotreated light No data available. Solvent naphtha (petroleum), light aliph. No data available. Acetic acid, methyl ester No data available. Maleic Anhydride Modified Liquid No data available.

Polyisoprene

Other adverse effects: Harmful to aquatic life with long lasting effects.

#### 13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

#### 14. Transport information

### DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): Packing Group: II
Marine Pollutant: No

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

Revision Date: 03/17/2020

#### **IMDG**

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): – EmS No.:

Packing Group: -

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): –

Packing Group: –

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

# 15. Regulatory information

#### **US Federal Regulations**

Restrictions on use: Not known.

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical IdentityOSHA hazard(s)BenzeneFlammability

Cancer Aspiration Eye Blood Skin

respiratory tract irritation Central nervous system

#### CERCLA Hazardous Substance List (40 CFR 302.4):

Reportable quantity
lbs. 100
lbs. 5000
lbs. 100
lbs. 100
lbs. 100
lbs. 5000
lbs. 1000
lbs. 1000
lbs. 10
lbs. 5000
lbs. 5000
lbs. 1000
lbs. 1000
lbs. 1000

Revision Date: 03/17/2020

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards

Flammable aerosol Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin sensitizer

Specific Target Organ Toxicity - Single Exposure

Aspiration Hazard

# **SARA 302 Extremely Hazardous Substance**

Reportable
------------

Chemical Identity	quantity	Threshold Planning Quantity
2-Propanone		
Acetic acid, methyl ester		
Hexane		
Phenol	lbs. 1000	

# **SARA 304 Emergency Release Notification**

Chemical Identity	Reportable quantity
Propane	lbs. 100
2-Propanone	lbs. 5000
Butane	lbs. 100
Heptane	lbs. 100
Acetic acid, methyl ester	lbs. 100
Methanol	lbs. 5000
Benzene, ethyl-	lbs. 1000
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10
Benzene, (1-methylethyl)-	lbs. 5000
Hexane	lbs. 5000
Cyclohexane	lbs. 1000
Phenol	lbs. 1000
Benzene, ethenyl-	lbs. 1000

#### SARA 311/312 Hazardous Chemical

Chemical Identity	<b>Threshold Planning Quantity</b>
Phenol	lbs
Propane	10000 lbs
2-Propanone	10000 lbs
Butane	10000 lbs
Heptane, branched, cyclic	10000 lbs
and linear	
Heptane	10000 lbs
Naphtha (petroleum),	10000 lbs
hydrotreated light	
Solvent naphtha	10000 lbs
(petroleum), light aliph.	
Acetic acid, methyl ester	10000 lbs
Maleic Anhydride Modified	10000 lbs
Liquid Polyisoprene	
Methanol	10000 lbs
Benzene, ethyl-	10000 lbs
Benzene, methyl-	10000 lbs
Benzene	10000 lbs
Benzene, (1-methylethyl)-	10000 lbs
Hexane	10000 lbs
Cyclohexane	10000 lbs
Benzene, ethenyl-	10000 lbs
· ·	

Revision Date: 03/17/2020

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

# Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

#### **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Methanol Developmental toxin. 03 2012

Benzene, ethyl- Carcinogenic. 05 2011

Benzene, methylBenzene

Developmental toxin. 03 2008
Developmental toxin. 03 2008

Benzene Carcinogenic. 05 2011

Benzene Male reproductive toxin. 03 2008

Benzene, (1-methylethyl)- Carcinogenic. 05 2011

Hexane Male reproductive toxin. 12 2017

Benzene, ethenyl- Carcinogenic. 04 2016

# US. New Jersey Worker and Community Right-to-Know Act

#### **Chemical Identity**

Propane

2-Propanone Butane

Naphtha (petroleum), hydrotreated light

Solvent naphtha (petroleum), light aliph.

Heptane

Acetic acid, methyl ester

# **US. Massachusetts RTK - Substance List Chemical Identity**

Dansan

Benzene

Phenol

#### US. Pennsylvania RTK - Hazardous Substances

# **Chemical Identity**

Propane

2-Propanone

**Butane** 

Naphtha (petroleum), hydrotreated light Solvent naphtha (petroleum), light aliph.

Heptane

Acetic acid, methyl ester

#### **US. Rhode Island RTK**

No ingredient regulated by RI Right-to-Know Law present.

#### International regulations

#### Montreal protocol

2-Propanone

Acetic acid, methyl ester

#### Stockholm convention

2-Propanone

Acetic acid, methyl ester

#### **Rotterdam convention**

2-Propanone

Acetic acid, methyl ester

Revision Date: 03/17/2020

#### **Kyoto protocol**

**Inventory Status:** 

Australia AICS: Not in compliance with the inventory.

Canada DSL Inventory List:

On or in compliance with the inventory

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: Not in compliance with the inventory.

China Inv. Existing Chemical Substances: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: Not in compliance with the inventory.

US TSCA Inventory: On or in compliance with the inventory

New Zealand Inventory of Chemicals: Not in compliance with the inventory.

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory:

Not in compliance with the inventory.

Taiwan Chemical Substance Inventory: Not in compliance with the inventory.

#### 16.Other information, including date of preparation or last revision

**Issue Date:** 03/17/2020

**Revision Information:** No data available.

Version #: 1.0

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.